30303

AUTO METER DASH HARNESS INSTALLATION INSTRUCTIONS

1. ALL RED CONNECTORS SHOULD BE ATTACHED TO THE LIGHT SOCKETS ON ALL THE GAUGES.

2. THE GRAY CONNECTORS SHOULD BE ATTACHED TO THE PROPER GAGE ACCORDING TO THE FOLLOWING CHART:

CONNECTORS WITH WIRE COLORS:	**GOES TO:**
RED/WHITE, BLACK, AND LT. BLUE	OIL PRESSURE
RED/WHITE, BLACK, AND LT GREEN	WATER TEMPERATURE
RED/WHITE, BLACK, AND PURPLE/WHITE	TACHOMETER
RED/WHITE, BLACK, AND PINK	FUEL LEVEL
RED/WHITE AND BLACK	VOLTMETER

3. THE WIRES IN THE CENTER THAT HAVE BUTT CONNECTORS ON THEM ARE FOR THE TURN SIGNAL AND HIGH BEAM INDICATOR LIGHTS (IF APPLICABLE). THE LT. BLUE AND BLACK PAIR IS FOR THE LEFT TURN INDICATOR. THE DARK BLUE AND BLACK PAIR IS FOR THE RIGHT TURN INDICATOR. THE DARK GREEN AND BLACK PAIR IS FOR THE HIGHBEAM HEADLIGHT INDICATOR.

4. THE PARTS BAG INCLUDED IN THIS KIT CONTAINS THE MATING PLUGS AND PINS FOR THE CONNECTORS ALREADY INSTALLED ON THIS HARNESS.

THE PINS SHOULD BE CRIMPED ONTO THE MAIN WIRING HARNESS AND INSERTED INTO THE LOOSE CONNECTORS ONE AT A TIME SO THAT THE FOLLOWING WIRES ARE CONNECTED TOGETHER ONCE THE TWO PLASTIC CONNECTORS ARE MATED TOGETHER:

WIRE IN DASH HARNESS	**IS CONNECTED TO :**
(ON NINE POSITION CONNECTOR)	
RED/WHITE	IGNITION ONLY (SWITCHED) +12 VOLT SOURCE
BLACK	GROUND
BROWN	HEADLIGHT SWITCH (DASH LIGHTS TERMINAL)
LT. GREEN	WATER TEMP SENDER
LT. BLUE	OIL PRESSURE SENDER
PURPLE/WHITE	TACH PICKUP
PINK	FUEL GAGE SENDING UNIT
DARK GREEN	HIGH BEAM INDICATOR WIRE
(ON TWO POSITION CONNECTOR)	
DARK BLUE	RIGHT TURN INDICATOR WIRE
LT. BLUE	LEFT TURN INDICATOR WIRE